

## LC Uniboot Patch Cord



### Description

- WCFO's LC Uniboot patch cord employs 1.25mm zirconia ceramic ferrules for either PC or APC applications, Provides optimum insertion and return loss. WCFO's LC Uniboot connector features round style 2.0mm, 2.4mm, and 3.0mm jacketed cables which reduce cable congestion and makes cable management easier in today's highly dense application. All cables are tested, serialized, and labeled in individual bags with complete test information.

### Features

- High density applications
- Snap-on locking element for easy and secure handling
- Crimp sets for tubes and cables
- Suited for high power applications
- Single mode PC ,UPC and APC and multimode
- Conforms to IEC61754-20
- Conforms to Telcordia GR-326-CORE
- All parts comply w/ RoHS 2.0 / REACH

### Application

- Telecommunication
- CATV
- LAN & WAN
- Network
- Broadband
- FTTP
- Data centers

### Parameter

Item	SM			MM
	PC	UPC	APC	/
Polishing Type	PC	UPC	APC	/
Insertion Loss	≤0.3dB			≤0.3dB
	Customize			
Return Loss	≤-45dB	≤-50dB	≤-60dB	/
	Customize			
Durability	0.2dB Max. Increase			
Operating Temperature	-40°C ~ +75°C			
Storage Temperature	-40°C ~ +75°C			

### Appearance & Dimension

